

# OPTONICA



**STRISCIA LED COB**  
**288 LED/m 220V**  
**RIVESTIMENTO**  
**BIANCO OPACO**  
**10W/m 50m/BOBINA**

## Potenza


- 10W/m

## Colore della luce



Luce naturale

## Stamps





## Specifiche tecniche

|                                     |               |
|-------------------------------------|---------------|
| <b>Numero di catalogo</b>           | 4955          |
| <b>Brand</b>                        | Optonica      |
| <b>Product Code</b>                 | ST228-A1      |
| <b>Power</b>                        | 10W/m         |
| <b>Energy Consumption</b>           | 10 kWh/1000h  |
| <b>Input voltage</b>                | AC220V        |
| <b>Flux</b>                         | 700 lm/m      |
| <b>IP</b>                           | 65            |
| <b>Dimmable</b>                     | Yes           |
| <b>Correlated Color Temperature</b> | 4500K         |
| <b>Light Color</b>                  | Luce naturale |
| <b>EAN Code</b>                     | 3800156649552 |
| <b>Energy Efficiency Label</b>      | G             |
| <b>Beam angle</b>                   | 120°          |

|                                                 |                 |
|-------------------------------------------------|-----------------|
| <b>On/Off Cycles</b>                            | 25 000x         |
| <b>Instant On</b>                               | 0.1s            |
| <b>Operating Frequency</b>                      | 50-60 Hz        |
| <b>Life span</b>                                | 25 000 Hours    |
| <b>LED Type</b>                                 | COB             |
| <b>Roll</b>                                     | 50 m.           |
| <b>Lumen maintenance at end of service life</b> | 70%             |
| <b>Size of product</b>                          | 12x6 mm         |
| <b>Material</b>                                 | Flex PCB        |
| <b>Operating Temperature</b>                    | -20°C/+40°C     |
| <b>Certificate</b>                              | IP65, CE & RoHS |
| <b>CRI</b>                                      | ≥ 80            |
| <b>Cutting distance</b>                         | 1M              |
| <b>Gross weight</b>                             | 0,080 kg        |
| <b>Net weight</b>                               | 0,080 kg        |
| <b>Warranty</b>                                 | 2 Years         |